




WORLD CLASS
EFFICIENCY & RELIABILITY



Air Cooled Direct Coupled Type Fixed / Variable Speed Screw Air Compressor (7.5kW-250kW)

HEXAone - HE Series

HEXAone HE Series DIRECT DRIVE compressors are designed to provide rock-solid reliability. A direct, semi-elastic coupling between the motor and air end provide excellent output. Each motor power has a specifically adaptable air end, which optimizes performance and reliability all the time.

Premium Efficiency IE3/IE4 Motor

World renowned electric motor manufacturer. High efficiency electric motor TEFC, IP55 class F with Service factor 1.2 and S1 duty fitted with high quality bearings from 'SKF'

Advanced Design Suction Valve

Advanced design suction control valve with automatic closure to prevent oil escape. Reliable and more durable.

Smart & Intelligent Controller

Simple to use, advanced sequence control, Built-in communication module RS-485 Touch screen for all models Modbus protocol as an option.

HEXAone

Karachi Office : 409, Business Arcade, Shahrah-e-Faisal Block-6, PECHS Karachi - Pakistan
Cell : 0345-0020356

Lahore Office :712-J2, Fatima Road Johar Town, Lahore - Pakistan

Email : info@hexaone.co Cell : 0347-7943563 - 0345-0020358

Website : www.hexaone.co



HEXAone HE Series Specification (Fixed / Variable Speed)

Model	Working Pressure (bar)	FAD m ³ /min	Power (KW)	Noise (dB(A)) ±3	Weight (kg)	Dimensions(mm)	Air Outlet Diameter
						LxWxH	
HE-10	8	1.1	7.5	62	240	850x630x970	G 3/4
	10	1.0					
	13	0.8					
HE-15	8	2.0	11	65	300	1100x750x1150	G 1
	10	1.6					
	13	1.2					
HE-20	8	2.4	15	65	330	1100x750x1150	G 1
	10	1.8					
	13	1.5					
HE-30	8	3.4	22	68	370	1350x895x1150	G 1
	10	3.2					
	13	2.8					
HE-40	8	5.0	30	68	495	1500x1000x1195	G 1 1/2
	10	4.5					
	13	3.8					
HE-50	8	6.2	37	70	505	1500x1000x1195	G 1 1/2
	10	5.4					
	13	4.8					
HE-60	8	7.2	45	70	560	1500x1000x1195	G 1 1/2
	10	6.2					
	13	5.8					
HE-75	8	9.2	55	72	950	1900x1300x1600	G 2
	10	8.0					
	13	7.2					
HE-100	8	12.5	75	72	1000	1800x1360x1665	G 2
	10	11.0					
	13	9.5					
HE-125	8	15.0	90	75	1900	2000x1535x1800	G 2
	10	13.0					
	13	12.0					
HE-150	8	19.0	110	75	1950	2100x1535x1800	DN 65
	10	16.0					
	13	15.0					
HE-175	8	22.0	132	78	2510	3200x1566x1800	DN 65
	10	20.0					
	13	18.5					
HE-200	8	26.5	160	78	3010	2800x1772x2180	DN 80
	10	23.0					
	13	20.5					
HE-250	8	32.0	185	78	3300	2660x1715x2020	DN 80
	10	29.0					
	13	26.0					
HE-350	8	42.0	250	80	4300	3800x2270x2300	DN 100
	10	38.0					
	13	35.6					

*Two stage & higher capacity machines are also available *The capacity (FAD_Free air delivery) Measured as per ISO1217, sound level measured ISO2151.

*The specifications are subjects to change without prior notice for our continuous improvment.

*Different voltage and frequency avallble on demand.

